

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets

(11)

Publication number:

**0 297 552  
A2**

(12)

## EUROPEAN PATENT APPLICATION

(21)

Application number: 88110394.9

(51)

Int. Cl. 4: **B23P 11/00**

(22)

Date of filing: 29.06.88

(30)

Priority: 01.07.87 JP 164848/87  
01.07.87 JP 164849/87  
01.07.87 JP 164850/87  
01.07.87 JP 164851/87  
01.07.87 JP 164852/87

(43)

Date of publication of application:  
04.01.89 Bulletin 89/01

(64)

Designated Contracting States:  
DE FR GB IT NL

(71)

Applicant: **KAWASAKI JUKOGYO KABUSHIKI  
KAISHA**  
1-1 Higashikawasaki-cho 3-chome  
Chuo-ku Kobe-shi Hyogo-ken(JP)

(72)

Inventor: Matsui, Shigetomo  
4-25, Higashiyama-Cho  
Higashiosaka-Shi Osaka-Fu(JP)  
Inventor: Matsumura, Hiroyuki  
2-1-35-402, Ryugadai, Suma-Ku  
Kobe-Shi Hyogo-Ken(JP)  
Inventor: Yamada, Takeshi  
4-19, Akibadai 3-Chome, Nishi-Ku  
Kobe-Shi Hyogo-Ken(JP)  
Inventor: Kumon, Yasuhiro  
14-9, Shioya-Cho 6-Chome, Tarumi-Ku  
Kobe-Shi Hyogo-Ken(JP)  
Inventor: Ryoji, Makoto  
Kawaju Shioya Ryo, 14-9, Shioya-Cho  
6-Chome  
Tarumi-Ku Kobe-Shi Hyogo-Ken(JP)  
Inventor: Uekado, Masaki  
17-6, Karibadai 2-Chome, Nishi-Ku  
Kobe-Shi Hyogo-Ken(JP)  
Inventor: Koe, Shigeki  
6-11, Takenodai 4-Chome, Nishi-Ku  
Kobe-Shi Hyogo-Ken(JP)  
Inventor: Asari, Hiroatsu 1406, Takakuradai  
Heights  
7-1, Takakuradai 7-Chome Suma-Ku  
Kobe-Shi Hyogo-Ken(JP)  
Inventor: Ishizuka, Toshihiko  
3-3-102, Iwazono-Cho  
Ashiya-Shi Hyogo-Ken(JP)  
Inventor: Atsuta, Toshio  
6-21, Uenomaru 2-Chome  
Akashi-Shi Hyogo-Ken(JP)  
Inventor: Murakami, Shigemi  
997-9, Kouzubashi, Tamatsu-Cho Nishi-Ku  
Kobe-Shi Hyogo-Ken(JP)

**EP 0 297 552 A2**

Inventor: Okazaki, Shozo  
 14-34, Nishikigaoka 2-Chome Uozumi-Cho  
 Akashi-Shi Hyogo-Ken(JP)  
 Inventor: Koga, Shinji 2-104, Kawaju  
 Nishisuzu Shataku  
 11, Minamigoyo 3-Chome Kita-Ku  
 Kobe-Shi Hyogo-Ken(JP)  
 Inventor: Yamamoto, Akitoshi  
 33-21, Kitaoji-Cho, Kamigamo Kita-Ku  
 Kyoto-Shi Kyoto-Fu(JP)

⑦ Representative: Klunker . Schmitt-Nilson .  
 Hirsch  
 Winzererstrasse 106  
 D-8000 München 40(DE)

⑤ Composite structures and methods of manufacturing the same.

⑤7 A composite structure is manufactured by joining a first material (2) preferably made of a magnetically permeable material having a first joining surface (11a) in which a recess (7) having an overhang surface (6) is formed, to a second material (3) preferably made of an electrically conductive material having a second joining surface (11b), to be joined to the first joining surface (11a) of the first material. On the second joining surface (11b), a protrusion (9) having an outer configuration substantially corresponding to the inner shape of the recess (7) is integrally formed. The first and second materials (2, 3) are firmly mechanically joined to each other by, for example, a casting method, a rolling method, a pressing method, or a method by utilizing a plastic flow of the second material (3).




FIG. 1A

## COMPOSITE STRUCTURES AND METHODS OF MANUFACTURING THE SAME

### BACKGROUND OF THE INVENTION

This invention relates to composite structures fabricated by joining materials of dissimilar or different kinds and relates also to methods of manufacturing the composite structure to be utilized, for example, as a secondary plate of a linear motor car railway track, for inducing electric driving force for such motor car.

As is well known, traffic facilities have occupied a significant and important position in the social life, and among various traffic facilities, transportation means such as railways play an important role in the rapid mass transportation apart from the transportation by means of automobiles.

However, as speeding up of the railway transportation has been desired, vibrations and noises caused by the transportation means has become factors which cannot be neglected in the social life. In another aspect, excavating and drilling operations as for a underground railway tunnel have become large scale ones with more and more increasing cost, and for this reason, development of a linear motor car capable of travelling along an iron railway track without generating violent vibrations or noises is highly desired and has been partially realized.

In connection with the linear motor car of the character described above, a structure of a secondary plate, which functions to produce eddy current, in a primary side of the motor car for producing a driving force, must be used on the railway track. Such secondary plate is required to have high electric conductivity and magnetic permeability as well as a great resistance against shearing forces and separating forces which are generated as counter forces against the great driving force. However, in the current technique, a single metal or metallic material having these characteristics has not been developed, and accordingly, a composite structure fabricated by tightly and firmly joining materials of different kinds having a high electric conductivity and a high magnetic permeability, respectively, is utilized as the secondary plates.

For example, there are known composite structures fabricated by fixedly joining face to face an aluminum plate having a high electric conductivity on a soft steel plate having a high magnetic permeability. In an example of such composite structures, the aluminum plate is press-fitted at the opposite ends thereof on the two end surfaces of the soft steel plate, and fastening screws are passed through the aluminum plate into the soft

steel plate to mechanically join both the plates as a combined metallic structure. In another example, a composite structure is obtained by joining the aluminum plate to the soft steel plate by an explosion bonding method into an explosion bonded clad plate.

However, as described hereinbefore, it is required for the secondary plate to possess a mechanical strength against the strong reacting forces to the driving force, acting frequently and repeatedly, and accordingly, the secondary plate must have a large resistance against shearing forces along the interface between the two elementary plates as well as against vertical separating forces imparted to the two elementary plates of the secondary plate. Particularly, when a composite structure is applied to the railway track of a subway, it is required for the composite structure to have mechanical strength or resistance against additional thermal behavior and separating forces due to temperature variations and dynamic vibrations. However, the composite structures fabricated by press-forming the two plates and then clamping by fastening screws or fabricated by the explosion bonding method cannot maintain sufficient resistance for a long period of time.

Particularly, the composite structure, in which an aluminum plate and a soft steel plate are mechanically joined by pressing them and clamping them by means of bolts, tends to be loosened as time elapses, while the explosion bonding method is extremely expensive, thus being not advantageous.

Moreover, when the composite structures of the characters described above are applied to the railway track of the subways, for example, sited near seashores, the railway tracks are exposed to severe environmental conditions such as corrosion or submergence and the interface between the soft steel plate and the aluminum plate are corroded. When corrosion occurs, the composite structure cannot attain the function as the secondary plate for the railway track.

### SUMMARY OF THE INVENTION

Accordingly, an object of this invention is to substantially eliminate defects or drawbacks encountered in the conventional technique described hereinbefore and to provide composite structures fabricated by materials of different kinds capable of maintaining for a long time firm mechanically joined condition of the different materials without

causing relative shifting and separation of the joined surfaces of the materials even when the composite structure is exposed to an environment in which repeatedly acting strong shearing stresses and violent thermal behavior are imparted to the composite structure.

Another object of this invention is to provide composite structures of the characters described above capable of being manufactured with low cost.

A further object of this invention is to provide various methods of manufacturing the composite structures of the characters described above.

These and other objects can be achieved, in one aspect according to this invention, by providing a composite structure fabricated from materials of different kinds, which structure comprises a first material provided with a first joining surface in which at least a recess having an overhang surface is formed, and a second material provided with a second joining surface joined face to face to the first joining surface, said second joining surface having thereon at least a protrusion having an underhang surface and formed integrally with the second material, the protrusion having a shape and demensions substantially corresponding to those of the recess and being firmly engaged with the recess in a manner fully filling the same.

In another aspect, according to this invention, there is provided a method of manufacturing a composite structure of the character described above, which method comprises the steps of preparing a first material with a first joining surface, having at least a recess having an overhang side surface, placing the first material in a casting mold in a manner to leave a space having a predetermined width between the first joining surface of the first material and an inner surface of the casting mold, pouring a second material in a molten state into the space to fill the second material into the recess of the first material and to bond a second joining surface of the second material entirely to the first joining surface of the first material, and taking the thus bonded first and second materials out of the casting mold.

According to this invention, there is further provided a method of manufacturing a composite structure fabricated from materials of different kinds, which method comprises the steps of preparing a first material having a first joining surface, forming at least a recess having an overhang side surface in the first joining surface of the first material, preparing a second material having a second joining surface, and opposing the first and second joining surfaces of the first and second materials and pressing the opposed first and second materials from one side thereof to cause plastic flow of the second material into the recess to cause the

second material to be filled into the recess of the first material.

According to this invention, there is still further provided a method of manufacturing a composite structure made from materials of different kinds, which method comprises the steps of preparing a first material having a first joining surface in which at least a recess in the shape of a local hole having an overhang surface is formed, preparing a second material having a second surface and provided with at least a local through hole having an underhang surface, placing the second material on the first material in such a manner that the first and second joining surface contact each other with the through hole of the second material aligning with the recess of the first material, inserting an anchoring material into the through hole and the recess, and plastically deforming the anchoring material to cause it to entirely fill the through hole and the recess.

According to this invention, there is still further provided a method of manufacturing a composite structure made from materials of different kinds, which method comprises the steps of preparing a first material having a first joining surface, forming at least a recess having an overhang surface in the first material, preparing a pair of second materials each in the shape of a plate, fixedly mounting the second materials on the first joining surface of the first material, the plates of the second materials having one ends opposing to each other with a space therebetween above the recess of the first material, filling a third material into the recess and a space between the opposed ends of the second materials to form a build-up weld, and removing the build-up weld such that an outer surface of the filled third material is flush with the outer surfaces of the second materials.

In preferred embodiments of this invention, the first material is made of a magnetically permiable material and the second material is made of an electrically conductive material.

The composite structure thus manufactured can provide a firm mechanically joined condition between the first and second materials by virtue of the firm engagement of the overhang surface of the recess of the first material with the underhang surface of the protrusion of the second material.

#### BRIEF DESCRIPTION OF THE DRAWINGS

In the accompanying drawings:

Fig. 1A is a cross sectional view of one embodiment of a composite structure comprising materials of different kinds according to this invention;

Fig. 1B is a cross sectional view of the materials, shown as being separated, of the composite structure shown in Fig. 1A;

Fig. 2 is a cross sectional view of another embodiment of the composite structure according to this invention;

Figs. 3 to 7 are cross sectional views of further embodiments of the composite structures, respectively, according to this invention;

Fig. 8 is a fragmentary perspective view of a still further embodiment of the composite structure according to this invention;

Figs. 9 and 10 are fragmentary perspective views illustrative of recesses formed in first materials of further embodiments according to this invention;

Fig. 11 is a plan view showing one example of a joining surface of a first material of the composite structure according to this invention;

Figs. 12 and 13 are end views as seen in the directions of arrows XII-XII and XIII-XIII of Fig. 11, respectively;

Fig. 14 is a perspective view showing a first material of a composite structure according to a still further embodiment of this invention;

Fig. 15 is a plan view of a first material similar to the first material shown in Fig. 14;

Figs. 16 and 17 are sections taken along the lines XVI-XVI and XVII-XVII shown in Fig. 15, respectively;

Fig. 18 is a sectional view illustrative of a composite structure in which a second material is firmly engaged with the material shown in Fig. 16;

Fig. 19 is a cross sectional view of a first material in which a recess is to be formed;

Fig. 20 is a cross sectional view showing a step to form a recess in the material shown in Fig. 19;

Fig. 21 is a cross sectional view representing a next step subsequent to the step shown in Fig. 20 to form the recess;

Fig. 22 is a cross sectional view showing a step to form a recess having a cross-sectional shape different from that shown in Fig. 20 in the material shown in Fig. 19;

Fig. 23 is a cross sectional view showing a next step subsequent to the step shown in Fig. 22 to form the recess;

Fig. 24 is a cross sectional view representing a step to form a recess in a surface of a first material of a composite structure according to a still further embodiment of this invention;

Fig. 25 is a plan view showing a portion of the first material in which a recess is formed by the step shown in Fig. 24;

Fig. 26 is a cross sectional view of one of materials constituting a composite structure shown in Fig. 4 representing a first step of forming a recess;

Figs. 27 and 28 are cross sectional views showing successive steps subsequent to the step shown in Fig. 26;

Figs. 29 to 31 are cross sectional views illustrative of steps in sequence of forming recesses in a first material constituting a composite structure, according to a method of this invention;

Fig. 32A is a perspective view of a first material of a composite structure according to a still further embodiment of this invention;

Fig. 32B is a fragmentary cross sectional view of the material shown in Fig. 32A;

Figs. 33A and 33B are views similar to Figs. 32A and 32B, respectively, showing a second material of the composite structure;

Figs. 34 to 36 are fragmentary cross sectional views illustrative of steps in sequence for joining the materials shown in Figs. 32A and 32B;

Fig. 37 is a fragmentary cross sectional view of a portion of a first material of a composite structure;

Fig. 38 is a plan view of a rotary cutter used for forming a recess shown in Figure 37;

Figs. 39 and 40 are views explanatory of steps in sequence of forming the recess by using the rotary cutter shown in Fig. 38;

Figs. 41 to 43 are views explanatory of steps in sequence of forming a recess in a first material of the composite structure, according to a still further method of this invention;

Figs. 44 to 48 are views explanatory of steps in sequence of forming a composite structure by a casting method for joining two different materials;

Figs. 49 to 52 are views explanatory of steps in sequence of joining two different materials due to plastic flow of a first material to form a composite structure;

Figs. 53 to 57 are views explanatory of other steps in sequence of joining two different material due to plastic flow of a first material to form a composite structure;

Figs. 58 to 62 are cross sectional views explanatory of steps in sequence of joining two different materials to form a composite structure of a still further character, according to a method of this invention; and

Figs. 63 to 65 are cross sectional views explanatory of modified steps of those shown in Figs. 58 to 62 in sequence of joining two different material to form a composite structure.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of this invention will be described hereunder with reference to a secondary plate of an iron track for a linear motor car railway in conjunction with the accompanying drawings.

Fig. 1A shows an embodiment of this invention in the form of a secondary plate 111 of an iron track, formed as a composite structure made of materials of dissimilar or different kinds. The composite structure comprises a soft steel plate 2 as a first material having a high magnetic permeability, and an aluminum plate 3 as a second material having a good electric conductivity and disposed on the soft steel plate 2, both plates 2 and 3 being joined mechanically along an interface 11.

Fig. 1B shows the composite structure in a state wherein the two plates 2 and 3 are separated. As is apparent from Fig. 1B the steel plate 2 is provided with an upper joining surface 11a in which are formed a plurality of grooves or recesses 7 each converging downwardly in cross section to form a V-shape and each being obliquely oriented so as to have one side surface 6 constituted as an overhang surface, which protrudes horizontally as it extends upwards as viewed in Fig. 1B. The angle of the oblique direction and the arrangement of the grooves 7 may be changed or modified in accordance with conditions of design.

The aluminum plate 3 is provided with a lower joining surface 11b on which are formed a plurality of projections or protrusions 9 each converging downwardly in cross section to form a V-shape and each obliquely projecting obliquely so as to have one side surface 8 constituted as an underhang surface which protrudes horizontally as it extends downwards as viewed in Fig. 1B.

The locations and shapes of the grooves 7 of the steel plate 2 are made to accord with those of the corresponding projections 9 of the aluminum plate 3 in the joined state. Although, in the illustration of Fig. 1B, the plates 2 and 3 are separated, actually these plates 2 and 3 are firmly mechanically joined together in the manufacturing process of the composite structure 111 according to this invention, for example, by casting the projections into the grooves 7 or by pressing the plate 3 against the plate 2 by means of a pressing roll to establish firm engagement of the projections 9 with the corresponding grooves 7 as described in detail hereafter.

The composite structure 111 can thus be formed integrally as one body with extremely high joining force and resistance against shearing forces in both the longitudinal and transverse directions, as well as against vertical separating forces based

on the thermal behavior due to temperature changes.

With the composite structure of the character described above, in a case where a linear motor car, not shown, travels above the secondary plate 111 with a predetermined height of floatation, eddy currents are generated through the aluminum plate 3, which produces a driving force for the linear motor car. During the travel of the car, the aluminum plate 3 receives a large reaction force as a result of the driving force in the longitudinal direction thereof. However, because of great resisting forces against the reaction forces and the shearing forces in a direction normal to the longitudinal direction and because of a great resistance in a vertical direction as viewed in Fig. 1A against separation of the two plates due to the strong mechanical engagement between the overhang surfaces 6 of the grooves 7 of the steel plate 2 and the underhang surfaces 8 of the projections 9 of the aluminum plate 3, the secondary plate is prevented from shifting in height more than a designed allowable change in height. In addition, the tight joining along the interface between the steel plate 2 and the aluminum plate 3 can positively prevent the possibility of corrosion which may be caused by salty sea winds or submergence by flooding and so on, whereby the two plates are prevented from separating, constantly maintaining the bonded condition originally designed, thereby enabling a linear motor car to travel as designed.

Fig. 2 shows another embodiment of a composite structure 112 according to this invention, in which all grooves or recesses 7 formed in the upper joining surface of the steel plate 2 have therein intermediate ridges or projections 10 directed upwardly to enlarge the joining surface area of the grooves 7 to thereby increase the resistance against the shearing forces. The composite structure 112 according to this embodiment is advantageous in that the projections 10 make easy plastic flows of the material of the aluminum plate 3 into the recesses 7, when the material of the plate 3 is to be pressed into the recesses 7, thus enabling better charging of the material of the plate 3 in the recesses 7.

Fig. 3 shows a further embodiment of the composite structure 113 according to this invention, in which the overhang surfaces 6 of the recesses of the steel plate 2 and the underhang surfaces 8 of the projections or protrusions 9 of the aluminum plate 3 are arranged in a symmetrical relation with respect to a plane along the line P-P, and in which the projections 9 extend obliquely in directions away from the plane along the line P-P. This embodiment of the composite structure 113 is effective in a case where the composite structure 113 is installed in a linear portion of a railway track, and is

advantageous in that it can be manufactured at low cost because of the symmetrical structure.

Fig. 4 shows a composite structure 114 according to a still further embodiment of this invention, in which the grooves or recesses 7 of the steel plate 2 and the projections or protrusions 9 of the aluminum plate 3 are both formed in a dovetail shape in cross-section with suitable distances between adjoining pairs of the recess 7 and the projection 9. The composite structure 114 according to this embodiment is advantageous in that it can be produced at low cost with a possibility of various design and arrangement of the recesses 7 and the projections 9.

Fig. 5 shows a composite structure 115 according to a still further embodiment of this invention, which has an arrangement of the grooves 7 of the steel plate 2 and the projections or protrusions 9 of the aluminum plate 3, similar to those shown in Fig. 1 but has waved overhang surface 6 and underhang surface 8 with minute pitches far smaller than those of the groove 7 and the projection 9 to facilitate firm engagement between the grooves 7 and the projections 9, whereby a strong bond between the steel plate 2 and the aluminum plate 3 can be obtained. According to this embodiment, a strong resisting force against shearing forces and separating forces which may be produced in curved portions of the railway track can be obtained.

Fig. 6 shows a composite structure 116 according to a still further embodiment of this invention, in which a layer 12 of thin plate made of an electrically insulating material is interposed between the joining surfaces of the soft steel plate 2 and the aluminum plate 3, instead of the direct contact of the metallic materials of different kinds constituting the metal plates 2 and 3 in the aforementioned embodiments. According to the construction of the composite structure 116 shown in Fig. 6, corrosion, which may be caused by an electric potential difference generated between both the plates 2 and 3, can be effectively prevented. In addition, since the steel plate 2 and the aluminum plate 3 are tightly joined through the layer 12, a sufficient resisting force against the shearing forces and separating forces can be obtained.

Fig. 7 shows a composite structure 117 according to a still further embodiment of this invention, in which a corrosion proof priming coat 12' is applied to the lower surface of the insulating layer 12 of the embodiment of Fig. 6 for increasing corrosion proof effect for the steel plate 2. In this embodiment, the corrosion proof coat may be applied to the upper surface of the insulating layer 12, and in a preferred modification a bonding agent having a corrosion proof characteristic may be ap-

plied instead of the corrosion proof coat.

The arrangements or orientations of the grooves or recesses 7 having the overhang surfaces 6 and the projections or protrusions 9 having the underhang surfaces 8 may be optionally made as shown in Figs. 8, 9 and 10, but not limited to these arrangements. In Fig. 8, the recesses 7 and projections 9 extend linearly in the same longitudinal or transverse direction. In Fig. 9, the recesses 7 and the projections not shown have a bent form. In Fig. 10, the recesses 7 and the projections not shown extend obliquely.

Figs. 11 and 13 shows a steel plate 2 of a composite structure 120 according to a still further embodiment of this invention, in which a plurality of grooves 7 are formed in the upper joining surface 11a of the steel plate 2 so as to linearly extend in parallel with each other, and each groove 7 has a cross sectional shape substantially the same as that shown in Fig. 2. A plurality of other grooves 14 are formed in the upper joining surface 11a of the steel plate 2 so as to extend in a direction to intersect the grooves 7, for example, in a direction normal to the grooves 7 as shown in Fig. 11. Figs. 12 and 13 are side views as seen in the directions of arrows XII and XIII of Fig. 11, respectively.

An aluminum plate 3 to be joined with the steel plate 2 shown in Fig. 11 has projections each having substantially the same configuration as that shown in Fig. 2 as well as underhang surfaces corresponding to the overhang surfaces 6 of the steel plate 2. The aluminum plate 3 of this embodiment is further provided with ridges to be firmly engaged with the grooves 14. According to this embodiment, the composite structure 120 is endowed with an increased resistance against external forces in the longitudinal direction of the groove 7 due to the existence of the additional grooves 14.

In a steel plate 2 of a composite structure 121 shown in Fig. 14, each groove 7 has protruding portions 16 in the shape of waves along the opening thereof. The wave-shaped protruding portions 16 can be formed, for example, by punched holes 15 shown in Figs. 15 to 17. The formation of the punched holes 15 deforms the inner walls of the grooves 7 near the opening thereof so as to partially form inward protrusions 16 in wave form as shown in Fig. 15. Figs. 16 and 17 illustrate cross sections of the steel plate 2 to show the shapes of the grooves 7 and the punched holes 15.

Fig. 18 shows a cross section of the composite structure 121 constructed by joining an aluminum plate 3 to the steel plate 2 shown in Fig. 14. According to this embodiment, the aluminum plate 3 are strongly joined with the steel plate 2 by virtue of the existence of the additionally provided punched holes 15.

The embodiments shown in Figs. 9 to 18 are

advantageous in that the resistance against shearing forces in all directions along the interface can be increased.

It should be noted that the composite structures of this invention have been described hereinbefore with reference to the preferred embodiments, but it is not limited to these embodiments and other various changes or modifications may be made. For example, ridges or grooves may be formed in zigzag shape on the underhang surfaces and overhang surfaces in plural stages in the direction of height of the protrusions and of the depth of the recesses, respectively. Further, the soft steel plate 2 and the aluminum plate 3 may be replaced with other metallic plate members of different kinds, respectively.

Moreover, the composite structures according to this invention can be used not only as a secondary plate of a linear motor car track but also as composite structures requiring firm engagement between two plates or members, for example, for use in motor cars, machine tools, or as composite structures which are used under severe, violent conditions accompanied by sliding movements, vibrations or temperature variations.

According to the composite structures of the characters described above, a firm engaging state between two materials can be maintained stably even under great, frequently repeated shearing and separating forces imparted to the composite structures, with the result that the function or operation of a linear motor car, for instance, can be stably maintained as designed. In addition, the joining surfaces of the two metal plates are kept in tightly bonded state in a manner of a labyrinth seal, so that separation of the two materials does not occur and any corrosive substance does not intrude to the interface even if the composite structure is exposed to corrosive atmosphere.

The formation of the V-shaped grooves 7 having overhang surfaces 6 in the joining surface of the soft steel plate 2 can be made in accordance with methods described hereunder with reference to the accompanying drawings.

In a first method, a blank soft steel plate 2 having a flat joining surface 11a to be bonded or joined, as shown in Fig. 19, is first prepared, and a formation roll 10 having flat opposite side surfaces and a circumferential surface provided therearound with a ridge formed so as to define a predetermined tapered peripheral surface is pressed with a predetermined pressure against the planar joining surface 11a of the steel plate 2 as shown in Fig. 20. When the formation roll 20 is rolled under the pressing condition, a sharply raised portion 24 is formed on the joining surface 11a at one side of the roll 20, as shown in Fig. 20, and simultaneously, a valley portion 25 and a slightly raised

portion 26 are also formed below the formation roll 20 and at the other side thereof, respectively. A valley portion 25 flanked by the raised portion 24 of a predetermined height is formed by repeating the pressing process described above by means of the formation roll 20.

In the next step, as shown in Fig. 21, when a cylindrical levelling roll 27 is rolled on the joining surface 11a in which the valley portion 25 has been formed by the pressing operation, the raised portions 24 and 26 are made flat so as to accord with the level of the other general portion of the joining surface 11a, whereby a V-shaped groove or recess 7 having the overhang surface 6 can be thus formed without carrying out a troublesome and difficult machining for cutting a sloping V-shaped groove.

A method of formation of a groove 7 having such a shape as shown in Fig. 2 will be described with reference to Fig. 22. In this method, a pulley-type formation roll 20a is pressed against the joining surface 11a of the blank soft steel plate 2 shown in Fig. 19. When the formation roll 20a is rolled on the joining surface 11a while pressing the same, a groove having an intermediate ridge 28, substantially vertical side walls and raised portions 29 is formed, and by repeating the rolling steps, a V-shaped valley portion for the groove and the raised portions 29 each having a predetermined height are formed.

In the next step, when a cylindrical formation roll 27a is rolled by a predetermined number of revolution on the valley portion of the joining surface 11a, the raised portions 29 are pressed into a flat state, and a groove having overhang surfaces 6 sloping outwards with respect to the ridge portion 28 can be formed.

Fig. 24 is explanatory of a further method of forming grooves 7 in the joining surface of the steel plate 2. In this method a pulley-type formation roll 20a similar to that shown in Fig. 22 is utilized. A plurality of depressions 30 are formed in the outer surface of the roll 20a so as to extend in the axial direction in circumferentially equally spaced relation. When the formation roll 20a is rolled on the joining surface of the steel plate 2, protrusions 31 are formed at equal intervals on the bottom of the groove 7 as shown in Fig. 25. Instead of the depressions 30, protrusions may be provided. In this case, depressions are formed in the bottom of the groove 7.

According to this embodiment, the projections of the aluminum plate 3 can be firmly engaged with the protrusions 31 when the aluminum plate 3 is joined with the steel plate 2, and accordingly, resistance of the grooves 7 against external forces in the longitudinal direction thereof is increased.

The formation of the groove 7 or the projection



9 having a dovetail cross-sectional shape as shown in Fig. 4 can be made in a manner shown in Figs. 26 to 28. A blank soft steel plate 2 having an upper joining surface 11a with a projection 40 preliminarily formed to have a rectangular cross section is first prepared. A formation roll 41 having therearound a groove of a substantially M-shaped cross section, as shown in Fig. 27, is pressed and rolled against the projection 40 in such a manner that the inner side walls of the M-shaped groove abut against the side walls of the projection 40. The formation roll 41 is rolled under the pressing condition by a predetermined number of revolution to plastically form the projection 40 into a M-shaped projection 40'. In the next step, a formation roll 42 having a cylindrical configuration is pressed against the M-shaped projection 40' and rolled by a predetermined number of revolution to form a projection 40'' having an upper flat surface and overhang surfaces 43 on both sides thereof, whereby the projection 40'' has a dovetail shape in cross section. According to this forming method, the dovetail-shaped projection can be easily formed as designed without carrying out a troublesome cutting work.

As will be easily understood, a dovetail-shaped projection having underhang surfaces on both sides thereof to be engageable with the overhang surfaces 43 of the steel plate 2 can be formed on the joining surface of the aluminum plate 3 in substantially the same manner as that described with reference to the formation of the dovetail-shaped projection 40'' of the steel plate 2.

Figs. 29 to 31 are explanatory of another method of forming grooves, each having a shape similar to that shown in Fig. 4, in the joining surface of the steel plate. According to this method, as shown in Fig. 29, a formation roll provided with annular roll portions 45 having a substantially rectangular cross-sectional shape is pressed against and then rolled on the joining surface 11a of the steel plate 2 to effect plastic working and to form grooves therein with raised portions 46 on both sides thereof.

In the next step, as shown in Fig. 30, a roll 48 provided with circumferential grooves 47 of a substantially triangular cross section at portions corresponding to the locations of the grooves 7 of the steel plate 2 formed by the formation roll 45 is pressed and rolled so as to plastically deform the raised portions 46 towards the insides of the grooves 7 as denoted by the reference numeral 46'. In the final stage, as shown in Fig. 31, when a formation roll 49 having a cylindrical configuration is pressed against and rolled on the joining surface 11a, the raised portion 46' are further deformed inwardly to thereby form the grooves 7 each having the overhang surfaces 6 on both sides.

Figs. 32 to 36 shows a still further composite

structure according to this invention and these figures are explanatory of a method of manufacturing this composite structure. Fig. 32A shows a soft steel plate 2 having local recesses 7 each in the form of a circular hole having an overhang surface 6 with a cross section shown in Fig. 32B instead of the groove shaped recesses mentioned hereinbefore with reference to the foregoing embodiments.

An aluminum plate 3 to be joined to the steel plate 2 shown in Fig. 32A is also provided with circular holes 51, as shown in Fig. 33A, each having an inverted frustconical cross section as shown in Fig. 33B. The location or arrangement of the holes 51 is of course designed to accord with the location of the recesses 7 of the steel plate 2 as shown in Fig. 34.

The thus prepared steel plate 2 and the aluminum plate 3 are superimposed in such a manner that the recesses 7 and holes 51 concentrically align with each other, and then an anchor material 52 made of a forgible soft material such as aluminum is inserted into each aligned pair of the hole 51 and recess 7 as shown in Fig. 35. The anchor material 52 is then deformed by, for example, forging to completely fill the holes 51 and the recesses 7 as shown at 52' in Fig. 36. The thus formed composite structure provides a firmly joined condition due to an anchoring effect. It is to be noted that the cross sections of the recess 7 and hole 51 need not be circular but can be rectangular, oval or of any other shape.

Fig. 37 shows a still further example of a steel plate 2 provided with recesses 7 each having a shape of a circular stepped hole with a lower portion having a diameter greater than that of an upper portion, the lower portion forming an overhang surface 6.

The formation of this hole 7 can be made by, for example, using a rotary cutter 55 of a type in which cutter blades 54 are shiftable between the positions shown by solid lines and the radially outwardly projecting positions shown by dotted lines in Fig. 38. In an actual operation, the rotary cutter 55 is placed on the joining surface 11a of the steel plate 2 and then rotated with the cutter blades 54 radially inwardly retracted to cut the plate 2 and form a circular hole as shown in Fig. 39. After the circular hole having a predetermined depth is formed, the cutter blades 54 are shifted or projected radially outwardly and again rotated to form an enlarged diameter hole portion as indicated in Fig. 40, thus forming a stepped hole as shown in Fig. 37.

A circular hole having such a cross section as shown in Fig. 32B may be formed by using the rotary cutter 55 while rotating the same with the cutter blades being radially outwardly moved

gradually.

Figs. 41 to 43 are explanatory of a still further method of the formation of the recesses 7 in the joining surface of the steel plate 2.

Referring to Fig. 41, a suppressing plate 58 provided with a plurality of circular holes 57 is first placed on the joining surface 11a of the steel plate 2, and in the next step, as shown in Fig. 42, a punch 60 having a diameter smaller than that of the hole 57 is inserted in the hole 57 and then thrust downwardly to form a punched hole in the steel plate 2. An annular raised portion 61 is formed along the periphery of the opening of the punched hole. Thereafter, the punch 60 is removed and a flat plate 62 is placed on the steel plate 2 and pressed downwardly to deform the raised portion 61 inwardly of the punched hole, thus forming a recess 7 having an annular overhang surface 6.

A steel plate 2 having grooves provided with the overhang surfaces formed by the methods described hereinbefore or a machining method can be firmly engaged or joined with an aluminum plate 3 having projections provided with the underhang surfaces in the manners and by the methods described hereunder.

In order to fabricate the composite structure of the character shown in Fig. 2, for example, the grooves 7 having the overhang surfaces 6 are first formed in the upper surface and, in a certain case, in both side surfaces, of the soft steel plate 2 as shown in Fig. 44, and thereafter, a pair of the thus prepared metal plates 2 are integrally bonded at the opposing back surfaces thereof through a release agent 63 such as plaster, as shown in Fig. 45, for the purpose of mass production of the composite structure. The thus bonded steel plates 2 are then placed in a casting mold 65 as shown in Fig. 46 and a molten aluminum bath 3' is poured through a gate 67 of the mold 65 into a cavity defined between the inner wall of the mold 65 and the outer joining surfaces and the side surfaces of the bonded steel plates 2. During this process, a care must be taken for entirely and completely charging the molten aluminum bath 3' over the entire overhang surfaces 6 of the grooves 7 of the steel plates 2.

The mold 65 is opened, after a predetermined time has elapsed to cool and coagulate the aluminum molten bath 3', to obtain a block in which the aluminum material 3 covers the entire outer surfaces of the steel plates 2 and is completely charged into all of the grooves 7 of the steel plates 2 along the overhang surfaces 6 thereof, as shown in Fig. 47. The block is then cut along the release agent 63 to obtain secondary plates such as shown in Fig. 48.

In the embodiment described above, an anticorrosion coating process can be interposed be-

tween the processes or steps carried out with reference to Figs. 45 and 46 to form a corrosion proof film made of an insulating material for preventing electrolytic corrosion between the steel and aluminum materials, on the joining surface between the steel plate 2 and the aluminum plate 3. The coated steel plates 2 are thereafter placed in the mold 65 and the molten aluminum bath 3' is poured into the mold cavity in the same manner as described before.

It should be course be understood that one of the two different materials which is more easily fusible than the other can be fused and poured into the mold in the molding process described hereinbefore.

Firm bonding or joining between the steel plate 2 and the aluminum plate 3 may be performed by a method utilizing plastic flow described hereunder.

Before carrying out this method, a soft steel plate 2 with a joining surface 11a having grooves 7 provided with overhang surfaces 6, as shown in Fig. 49, is first prepared, while a flat aluminum plate 3 having a joining surface 11b as shown in Fig. 50 is prepared.

The thus prepared plates 2 and 3 are superimposed with their joining surfaces 11a and 11b opposed as shown in Fig. 51 and the two plates are pressed entirely uniformly by means of a pressing device or rolling device, not shown, in the arrowed direction F.

The application of the pressure in the direction F causes plastic flow of the aluminum material forming the joining surface 11b of the aluminum plate 3, which has a yielding point lower than that of the steel plate 2, into the grooves 7 thereof, and continuous application of the pressure causes the aluminum material of the joining surface 11b to completely fill the grooves 7 along the entire overhang surfaces 6 thereof to achieve firm engagement of both the plates 2 and 3, which is maintained even after the pressing force has been released.

The plastic flow of the material of the aluminum plate 3 into the grooves 7 of the steel plate 2 will be assisted by heating the joining surface 11b of the aluminum plate 3 by means of a high frequency heating device, for example, during the pressure application process.

A final product can be obtained by carrying out a trimming operation on the thus obtained composite block of the plates 2 and 3.

The composite structure 112 shown in Fig. 2 can also be manufactured by a method described below with reference to Figs. 53 to 57.

According to this manufacturing method, a soft steel plate 2 having a joining surface 11a in which grooves 7 provided with overhang surfaces 6 are formed preliminarily is first prepared as shown in

Fig. 53, while an aluminum plate 3 having a joining surface 11b on which projections 66 are preliminarily formed at positions corresponding to the grooves 7 as shown in Fig. 54 is prepared. The tip end of each projection 66 is formed with a groove 67 of V-shaped cross section. This shape of the projections 66 is substantially the same as the projection 40' formed in the process step shown in Fig. 27. The aluminum plate 3 of Fig. 54 can be obtained as a section of the desired profile available in the market. It is desirable that the volumetric amount of each projection 66 on the joining surface 11b be slightly greater than the volumetric amount of each groove 7 of the steel plate 2.

In the next step, as shown in Fig. 55, the aluminum plate 3 and the metal plate 2 are arranged to oppose to each other so as to achieve a positional alignment of the corresponding projections 66 and grooves 7, respectively. Thereafter, the tip end of each projection 66 is fitted into each groove 7 as shown in Fig. 56, and a pressing force F is applied uniformly to the entire aluminum plate 3 towards the metal plate 2 by means of a pressing device or rolling device. The application of the pressing force F causes plastic flow of the aluminum material forming the projections 66 of the aluminum plate 3 as described with reference to the former embodiment, and the aluminum material of the projections 66 is charged into the grooves 7 of the steel plate 2 along the entire overhang surfaces 6 as shown in Fig. 56.

During this pressure application process, the plastic flow of the aluminum material into the grooves 7 along the overhang surfaces 6 can be more effectively achieved by a cotter function due to the presence of the inclined surfaces of projections formed on the bottoms of the grooves 7. In addition, the plastic flow of the material of the aluminum plate 3 upon the application of the pressing force F can be attained more precisely due to the fact that the volumetric amount of each projection 66 on the joining surface 11b of the aluminum plate 3 is designed to be slightly greater than the volumetric amount of the corresponding groove 7, whereby firm mechanical engagement between the aluminum plate 3 and the steel plate 2 is realized.

The plastic flow of the aluminum material can be effected more precisely by heating the projections 66 to a predetermined temperature to reduce the yielding stress of the aluminum plate 3 during the pressure applying process as described with reference to the former embodiment. Furthermore, even after the projections 66 has contracted due to the cooling during the pressure applying process, complete filling of the aluminum material in the grooves is attained since the volumetric amount of the projections 66 is made slightly greater than that of the grooves 7. That is, the flow of the aluminum

material into the grooves 7 after the contraction can be achieved without leaving vacant spaces or gaps therebetween, thus enabling to attain firm mechanical engagement between the aluminum plate 3 and the steel plate 2.

In the thus manufactured composite structure, since the joining area of the aluminum plate 3 to the soft steel plate 2 is enlarged, the composite structure can be endowed with a strong resisting force against the horizontal shearing displacement and the vertical separating displacement.

A still further joining method for manufacturing a composite structure will be described with reference to Figs. 58 through 62.

A soft steel plate 2, as shown in Fig. 58, is preliminarily prepared, which plate has stands 70 for attaching the plate 2 to a tie of the railway track for a linear motor car. A groove 7 is formed in the upper joining surface 11a of the steel plate 2 so as to have overhang surfaces 6 extending centrally in the longitudinal direction of the plate 2. A pair of grooves 71 each having an arcuate cross section are formed in both side surfaces of the plate 2.

In the next step, as shown in Fig. 59, a bar-like member 72 made of aluminum material having a trapezoidal cross sectional shape corresponding to that of the groove 7 shown in Fig. 58 is press fitted longitudinally into the groove 7. Alternatively, molten aluminum bath may be cast into the groove 7 to form an aluminum bar integral with the steel plate 2 instead of the fitting of the preliminarily made aluminum bar 72.

A pair of aluminum plates 3 are prepared, each in substantially L-shaped cross section having on one end a bead 73 engageable with the groove 71 and at the other end a tapered end surface 74. The thus prepared aluminum plates 33 are preliminarily heated and expanded by the heating to a predetermined temperature and then mounted on the upper surface of the steel plate 2 in such a manner that the respective beads 73 are engaged with the corresponding grooves 71 of the steel plate 2 and the tapered end surfaces 74 are positioned above the overhang surfaces 6 in an opposing state to each other with a space interposed therebetween as shown in Fig. 60.

In the next step, as shown in Fig. 61, an aluminum material is welded into the space defined above the upper surface of the aluminum bar 72 between both the tapered end surfaces of the aluminum plates 3 so as to form a build-up weld 74a to thereby integrally join the steel plate 2, the aluminum bar 72 and the aluminum plates 3 through the build-up weld 74a.

After these processes, the thus joined structure is disposed as it is to cool the same, and during the cooling process, the aluminum plates 3 contract in the width directions due to the cooling of

the plates 3 and the thermal contraction of the build-up weld 74a. As a result, the beads 73 of the aluminum plates 3 strongly engage or bite into the grooves 71, thus achieving firm engagement between the aluminum plates 3 and the steel plate 2. Finally, a surface finish working such as finish cutting is effected to the build-up weld 74a to obtain a secondary plate as a final product such as shown in Fig. 62.

The secondary plate as a final product provides a firm engagement of the aluminum plates 3 with the steel plate 2, which can be maintained for a long time and also provides a strong resisting force against shearing deformation in a horizontal direction and separating forces in a vertical direction.

A further modified method of manufacturing a composite structure will be described hereunder with reference to Figs. 63 to 65, in which like reference numerals are used to designate portions or members corresponding to those shown in Figs. 58 to 62.

As shown in Fig. 63, in this modification, the bar like aluminum member is not fitted in the groove 7 having the overhang surfaces 6 centrally extending in the longitudinal directions of the steel plate 2. A pair of aluminum plates 3 are placed on the upper joining surface 11a of the plate 2 in such a manner that each of the aluminum plates 3 has one end (bead) 73 engaged with the side groove 71 of the steel plate 2 and the other end 76 formed as a flanged portion projecting into the groove 7. In the next step, as shown in Fig. 64, an molten aluminum bath 77 is filled to form a build-up portion in and above a space defined by both the flanged portions 76 and the inner wall of the groove 7. The bath 77 is left as it is until it cools. The aluminum plates 3 can be thermally contracted during the cooling process by preliminarily heating the same, and due to the contraction, the beads 73 firmly bite into the grooves 71 to realize firm mechanical engagement between the aluminum plates 3 and the steel plate 2, which are, on the other hand, bonded through the solidified bath 77.

A surface finishing working such as finish cutting is performed as shown in Fig. 65 to obtain a flush surface of the aluminum plates 3 and the solidified bath, whereby there is obtained a composite structure as a final product of substantially the same character as that of the composite structure shown in Fig. 61 with the excellent or superior structural advantages described hereinbefore with respect to the former embodiments.

The methods of forming the recesses in the first material, as described hereinbefore, can be used in any type of the composite structures described hereinbefore.

## Claims

1. A composite structure made from a pair of materials of different kinds mechanically joined together, characterized in that it comprises:

a first material (2) provided with a first joining surface (11a) in which at least a recess (7) having an overhang surface (6) is formed; and

a second material (3) provided with a second joining surface (11b) joined face to face to said first joining surface (11a), on which second joining surface at least a protrusion (9) having an underhang surface (8) is integrally formed, said protrusion (9) having a shape and dimensions substantially corresponding to those of said recess (7) and being firmly engaged with the recess in a manner fully filling the same.

2. The composite structure according to claim 1 wherein said recess (7) has a substantially V-shaped cross section obliquely extending so as to have the overhang surface (6) on one side wall of said recess, and said protrusion (9) has a substantially V-shaped cross section obliquely extending so as to have the underhang surface (8) on one side wall of said protrusion corresponding to said overhang surface.

3. The composite structure according to claim 1 wherein said recess (7) has a dovetail-shaped cross section having two overhang surfaces (6) on both sides thereof and said protrusion (9) has the same dovetail-shaped cross section having two underhang surfaces (8) on both sides thereof corresponding to said overhang surfaces.

4. The composite structure according to claim 1 wherein said recess (7) and said protrusion (8) are formed with fine recesses and protrusions in wave form on the surfaces thereof.

5. The composite structure according to claim 4 wherein the joining surfaces (11a, 11b) of the first and second materials (2, 3) are at least partially formed with fine recesses and protrusions in wave form.

6. The composite structure according to claim 1 wherein said recess (7) is a groove and said protrusion (9) is a ridge.

7. The composite structure according to any one of claims 1 to 6 wherein said joining surfaces (11a, 11b) inclusive of an inner surface of said recess (7) and an outer surface of said protrusion (9) are joined to each other with a thin film (12) interposed therebetween.

8. The composite structure according to claim 7 wherein said thin film (12) comprises a corrosion proof coat.

9. The composite structure according to claim 1 wherein said recess (7) is a local hole and said protrusion (9) is a local projection.

10. The composite structure according to claim 1 wherein said recess (7) comprises a groove and a further groove (14) is formed in the joining surface (11a) of said first material (2) so as to intersect with said first mentioned groove and wherein said protrusion (9) comprises a ridge, and a further ridge having an outer configuration corresponding to that of said further groove is formed on the joining surface (11b) of said second material.

11. The composite structure according to claim 1 wherein said recess (7) is a groove and a plurality of projections or depressions (30) are formed on a bottom of the groove (7) at intervals.

12. The composite structure according to claim 1 wherein said recess (7) is a groove which has wave-shaped side edges (16) along the opening thereof.

13. The composite structure according to any one of claims 1 to 12 wherein there are provided a number of recesses (7) in the form of a groove in the first joining surface (11a) of the first material (2) and the directions of extension of the grooves are not uniform.

14. A method of manufacturing a composite structure made from a pair of materials of different kinds mechanically joined to each other, characterized by the steps of:

preparing a first material (2) having a first joining surface (11a);

forming at least a recess (7) having an overhang surface in the first joining surface (11a) of said first material (2);

preparing a second material (3) having a second joining surface (11b); and

opposing said first and second joining surfaces (11a, 11b) of said first and second materials and pressing the opposed first and second materials (2, 3) from one side thereof to cause plastic flow of said second material (3) into the recess (7) to cause the second material (3) to be filled into the recess.

15. The method according to claim 14 wherein said second material (3) is provided with a projection (66) formed on the second joining surface (11b), and the second material (3) is placed on the first material (2) such that said projection (66) of the second material opposes to said recess (7) of the first material, and wherein said first and second materials (2, 3) are mutually pressed to cause said projection (66) to plastically flow into said recess (7) thereby to mechanically join said first and second materials.

16. The method according to claim 14 or 15 wherein the recess (7) of said first material is formed in the shape of a groove so as to have a fork-shaped cross section and the projection (66) of

said second material is formed so as to have in a tip end thereof a groove (67) of a V-shaped cross section.

17. The method according to any one of claims 14 to 16 wherein said step of forming a recess comprises the steps of forming a groove having raised portions (24, 26) along the two sides thereof by rolling a formation roll (20) having a circumferential ridges, on the first joining surface (11a) of said first material, and forming a recess (7) of groove shape having an overhang side surface (6) by rolling a cylindrical roll (27) on said first joining surface (11a) to level said raised portions (24, 26).

18. The method according to any one of claims 14 to 17 wherein said step of forming a recess comprises the steps of forming a groove having a bottom surface with an intermediate protruding portion (28) and having raised portions (29) along the two sides thereof by rolling a formation roll (20a) having a circumferential groove of V-shaped cross section, on the first joining surface (11a) of said first material, and forming a recess of groove shape having overhang surfaces (6) on both side walls to provide a fork-shaped cross section by rolling a cylindrical roll (27a) on said first joining surface to level the raised portions (29).

19. The method according to any one of claims 14 to 18 wherein said formation roll (20a) is provided with a circumferential surface along which a plurality of recesses (30) or protrusions are formed at intervals.

20. The method according to any one of claims 14 to 19 wherein said step of forming a recess comprises the steps of forming a groove having raised portions (46) along both sides of an opening of the groove by rolling a pulley-type formation roll (45) on said first joining surface of said first material (2), deforming the raised portions (46) inwardly centrally of said groove by rolling on the first joining surface inclusive of the raised portions a roll (48) having a circumferential groove (47) of triangular cross-sectional shape with the triangular groove (47) confronting the raised portions (46') and forming a recess of groove shape having overhang surfaces (6) on both side thereof by rolling a cylindrical roll (49) on said first joining surface inclusive of the groove so as to level the raised portions (46').

21. A method of manufacturing a composite structure made from a pair of materials of different kinds mechanically joined to each other, characterized by the steps of:

preparing a first material (2) having a first joining surface (11a);

forming at least a recess (7) having an overhang surface (6) in the first joining surface (11a) of said first material;

placing said first material (2) in a casting mold

(65) in a manner to leave a space having a predetermined width between the joining surface of said first material (2) and an inner surface of the casting mold (65):

pouring a second material (3') in a molten state into said space to fill the second material into said recess and to bond a second joining surface of the second material entirely to the first joining surface of said first material (2); and

taking the thus bonded first and second materials out of the casting mold.

22. The method according to claim 21 wherein said step of forming a recess comprises the steps of forming a groove having raised portions (24, 26) along the two sides thereof by rolling a formation roll (20) having a circumferential ridges, on the first joining surface (11a) of said first material, and forming a recess of groove shape having an overhang side surface (6) by rolling a cylindrical roll (27) on said first joining surface (11a) to level said raised portions (24, 26).

23. The method according to claim 21 or 22 wherein said step of forming a recess comprises the steps of forming a groove having a bottom surface with an intermediate protruding portion (28) and having raised portions (29) along the two sides thereof by rolling a formation roll (20a) having a circumferential groove of V-shaped cross section, on the first joining surface (11a) of said first material, and forming a recess of groove shape having overhang surfaces (6) on both side walls to provide a fork-shaped cross section by rolling a cylindrical roll (27a) on said first joining surface to level the raised portions (29).

24. The method according to any one of claim 21 to 23 wherein said formation roll (20a) is provided with a circumferential surface along which a plurality of recesses (30) or protrusions are formed at intervals.

25. The method according to any one of claims 21 to 24 wherein said step of forming a recess comprises the steps of forming a groove having raised portions (46) along both sides of an opening of the groove by rolling a pulley-type formation roll (45) on said first joining surface of said first material (2), deforming the raised portions (46) inwardly centrally of said groove by rolling on the first joining surface inclusive of the raised portions a roll (48) having a circumferential groove (47) of triangular cross-sectional shape with the triangular groove (47) confronting the raised portions (46') and forming a recess of groove shape having overhang surfaces (6) on both side thereof by rolling a cylindrical roll (49) on said first joining surface inclusive of the groove so as to level the raised portions (46').

26. A method of manufacturing a composite structure made from materials of different kinds mechanically joined to each other, characterized by the steps of:

preparing a first material (2) having a first joining surface (11a);

forming at least a recess (7) having an overhang surface (6) in said first material;

preparing a pair of second materials (3) each in the shape of a plate;

fixedly mounting said second materials (3) on said first joining surface (11a) of the first material (2), said plates of the second materials having one ends (74) opposing to each other with a space therebetween above said recess (7) of the first material;

filling a third material (72, 75) into said recess and a space between the opposing ends of said second materials to form a build-up weld; and

removing the build-up weld such that an outer surface of the filled third material is flush with the outer surfaces of said second materials.

27. The method according to claim 26 wherein the opposing ends of said second materials (3) in the shape of a plate are provided with flanged portions (76) projecting inwardly of said recess of the first material (2).

28. The method according to claim 27 wherein said second materials (3) in the shape of a plate having the other ends provided with inward beads (73) respectively and wherein said first material (2) has side surfaces in which are formed recesses (71) with which said beads (73) are engaged to mechanically join the second materials to the first material.

29. The method according to any one of claims 26 to 28 wherein said step of forming a recess comprises the steps of forming a groove having raised portions (24, 26) along the two sides thereof by rolling a formation roll (20) having a circumferential ridges on the first joining surface (11a) of said first material, and forming a recess (7) of groove shape having an overhang side surface (6) by rolling a cylindrical roll (27) on said first joining surface (11a) to level said raised portions (24, 26).

30. The method according to any one of claims 26 to 29 wherein said step of forming a recess comprises the steps of forming a groove having a bottom surface with an intermediate protruding portion (28) and having raised portions (29) along the two sides thereof by rolling a formation roll (20a) having a circumferential groove of V-shaped cross section, on the first joining surface (11a) of said first material, and forming a recess of groove shape having overhang surfaces (6) on both side walls to provide a fork-shaped cross section by rolling a cylindrical roll (27a) on said first joining surface to level the raised portions (29).

31. The method according to any one of claims 26 to 30 wherein said formation roll (20a) is provided with a circumferential surface along which a plurality of recesses (30) or protrusions are formed at intervals.

5

32. The method according to any one of claims 26 to 31 wherein said step of forming a recess comprises the steps of forming a groove having raised portions (46) along both sides of an opening of the groove by rolling a pulley-type formation roll (45) on said first joining surface of said first material (2), deforming the raised portions (46) inwardly centrally of said groove by rolling on the first joining surface inclusive of the raised portions a roll (48) having a circumferential groove (47) of triangular cross-sectional shape with the triangular groove (47) confronting the raised portions (46') and forming a recess of groove shape having overhang surfaces (6) on both side thereof by rolling a cylindrical roll (49) on said first joining surface inclusive of the groove so as to level the raised portions (46').

10

15

20

33. A method of manufacturing a composite structure made from a pair of materials of different kinds mechanically joined to each other, characterized by the steps of:

25

preparing a first material (2) having a first joining surface (11a) in which at least a recess (7) in shape of a local hole having an overhang surface (6) is formed;

30

preparing a second material (3) having a second surface and provided with a local through hole (51) having an underhang surface;

placing said second material (3) on said first material in such a manner that said first and second joining surface contact each other with the through hole (51) of said second material aligning with the recess (7) of said first material;

35

inserting an anchoring (52) material into said through hole and recess; and


40

plastically deforming said anchoring material (52') to cause it to completely fill said through hole and recess.


45

50

55



**FIG. 1A**



**FIG. 1B**




FIG. 2




FIG. 3




FIG. 4.




FIG. 5






FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

FIG. 19




FIG. 20




FIG. 21




FIG. 22





FIG. 23






FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32 A




FIG. 32 B




FIG. 33 A




FIG. 33 B




FIG. 34




FIG. 35







FIG. 36




**FIG. 37**




**FIG. 38**




**FIG. 39**




**FIG. 40**



**FIG. 41**



**FIG. 42**



**FIG. 43**

FIG. 44




FIG. 45




FIG. 46




FIG. 47





FIG. 48








FIG. 49




FIG. 50




FIG. 51




FIG. 52



FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 64




FIG. 65